



BUILDING TRUST



PRODUCT DATA SHEET

QuietJoint®

Mass-Loaded Acoustic Partition Closure



QuietJoint SHH coated two-sides
QuietJoint SHG coated three-sides

Product Description

QuietJoint by Sika Emseal is a sound, draft, heat, cold, and dust blocking acoustic partition closure and joint filler for interior, non-moving joints and gaps.

It is a non-mechanical, high-STC (Sound Transmission Class), non-invasively anchored closure that quickly and easily mates partitions to windows, mullions, or stud walls. QuietJoint also blocks sound transmission between rooms.

This product is colorized*, versatile, and ideally suited as a closure for gaps between the ends of permanent, semi-permanent, or movable partitions, window-wall, curtain-wall, head-of-wall and other conditions.

QuietJoint features a mass-loaded fire-resistant foam core coated with commercial-grade silicone. The foam core is a custom-density open-cell foam infused with a fire-resistant, acrylic-based mass-loading agent.

Uses and Applications

- End of partition to mullion (SHH 2-sided coating)
- End of partition to window (SHG 3-sided coating)
- End of partition to wall (SHH)
- Head of wall (SHH)
- To block any flanking path
- To fill construction-created voids and gaps

Colors

- Available in many industry standard colors
- Custom colors
- 3-sided SHG is manufactured with the same color on all three sides.
- *QuietJoint is also available in a paintable STPE sealant coating in a single neutral "limestone" color ideal for accepting latex and acrylic paints and coatings on the exposed face.


Features

- Mass-loaded acoustic seal (STC-53, OITC-38, ASTM E-90)
- Fire-resistant (Smoke and Flame Spread Class A, ASTM E-84-12)
- **Insulates** (R-value 2.85/in depth, ASTM C-518-04)
- **Sound attenuating**
- Non-mechanical
- Non-metallic
- Rapid installation--new or retrofit
- Non-invasive anchoring
- Practical and versatile
- Easily handles curves
- Helps control HVAC balance between rooms


Material Configuration

QuietJoint comes coated on either 2 sides (SHH) or 3 sides (SHG).

SHH (two-sided silicone or paintable STPE) is ideal for gaps between opaque or solid partitions, walls or mullions.





SHG (three-sided silicone or paintable STPE) is typically used to fill gaps between the glass of curtainwall or windows on one side and solid substrates on the other. The third coating aesthetically covers the foam core so that the foam is not visible from the outside through the glass.



Sound Attenuation

Independent laboratory tested to control passage of air-borne sound.



Independent laboratory tested to ASTM E90-09, "Standard Test Method for Laboratory Measurement of Airborne Sound Transmission Loss of Building Partitions and Elements".

Insulation Value

QuietJoint helps to control HVAC balance and energy loss between rooms.

The **R-value** of QuietJoint foam is R-2.848/inch of depth.

Depending on the joint size and related depth, the R-value of the material will be:

Material	R-Value (Installed one side of joint)	R-Value (Installed both sides of joint)
1" to 4 3/4" width with 2" depth (25mm to 120mm with 50mm depth)	5.696	11.39+ *
5" to 6" width with 3" depth (125mm to 150mm with 75mm depth)	8.544	17.09+ *

**Assumes installation from both sides of the wall thereby doubling the R-value. The inclusion of an air gap between the two pieces of QuietJoint will add additional insulation, effectively more than doubling the R-value.*

Independent laboratory tested to ASTM C518-04 "Standard Test Method for Steady-State Thermal Transmission Properties by Means of the Heat Flow Meter Apparatus".

EMSEAL JOINT SYSTEMS, LTD
25 Bridle Lane
Westborough, MA 01581 USA
Phone: 508.836.0280
Fax: 508.836.0281
www.emseal.com

EMSEAL, LLC
111 Royal Group Crescent
Woodbridge, ON L4H 1X9 Canada
Phone: +1-416-740-2090
Fax: +1-416-740-0233
www.emseal.com

SIKA CORPORATION
201 Polito Avenue
Lyndhurst, NJ 07071 USA
Phone: +1-800-933-7452
Fax: +1-2019336225
www.usa.sika.com

Product Data Sheet
Emseal QuietJoint
October 2022 Version SE-1.1

Standard Sizes

Available in 1/4-inch increments for field-measured joint opening widths of 1-inch (25mm) to 6-inch (150mm). Supplied as either 6.56-foot (2M) or 10-ft (3M) length [which allows installation in most locations without any joins]. When QuietJoint is supplied in full-story, 10-foot (3-meter) lengths, it is shipped in loosely laid coils inside a cardboard box.

Joint Widths	Depth of Seal
1" - 4.75" (25 - 120mm)	2" (50mm)
5" - 6" (125 - 150mm)	3" (75mm)

Installation Overview

QuietJoint is supplied slightly larger than the field-measured joint gap. Being careful not to stretch it, the material is laid out and cut to the desired length. QuietJoint is positioned over the joint opening and squeezed by hand to ease it into the joint. The silicone coating folds at its edges to absorb slight variations in substrates while maintaining a smooth appearance. Once in desired location, a plastic putty knife is used to tuck the edges of the silicone against the substrates to remove any wrinkles. The internal backpressure of the material mates it to the mullion or other joint faces. In higher end finish applications QuietJoint can be installed behind finish trim (by others) to achieve a desired aesthetic.

Performance Limitations

Overcompressing QuietJoint can result in backpressure that could exceed the ability of certain substrates to resist this pressure. User is assumed to have tested all applications to ensure suitability for use.

Not intended for use in moving joints. Not trafficable. For watertight, moving structural joint gaps contact EMSEAL for product selection.

Availability & Price

QuietJoint is available for shipment internationally. Prices are available from local representatives and/or directly from the manufacturer. The product range is continually being updated, and accordingly EMSEAL® reserves the right to modify or withdraw any product without prior notice.



BUILDING TRUST

